



The Ultimate Protective Solution

SP PU COAT 600

TECHNICAL DATA

A single pack Polyurethane fast drying paint .

INTEDED USES

This versatile Fast drying paint is useful for interior & outdoor applications. This high glossy paint is recommended to OEM's, Fabricators, Architectural applications, Furnitures, Automobiles etc.

PHYSICAL PROPERTIES

Colour	: Full range
Finish	: Smooth & Glossy / semi glossy / matt
Flash Point	: Above 25 ⁰ C
Thinner intake	: 5 to 10 %
Recommended D.F.T.	: 25-30 µm per coat.
Drying time @ 30°C & at recommended D.F.T.	: a) Surface Dry : 5-10 Minutes b) Hard dry : 48 hrs.
Over coating Interval	: 4 to 24 hrs. @ 30°C
Recommended Thinner	: T 2000 for thinning & equipment cleaning
Shelf life	: 12 months (Individual sealed components under normal storage condition)
Theoretical Coverage	: 14m ² /litre on smooth & non-absorbent surface @ recomd. DFT
Application method	: By conventional Spray
Compatibility	: Compatible to Alkyd, Epoxy, PU primers.

SURFACE PREPARATION :

Prepare the primered surface by sanding with the suitable emery paper for better inter-coat adhesion with finish paint. (If primer has been cured for more than 24 hrs.)

ADDITIONAL NOTES :

This product should preferably be applied at temperatures in excess of 10⁰ C. Do not apply when relative humidity rises above 90%. Do not apply during rain, fog or mist. Numerical values quoted for physical data vary slightly from batch to batch & against the temperature.

DISCLAIMER : The information in this data sheet is given to the best of our knowledge based on laboratory testing & practical experience. It is the user's responsibility to conduct all necessary trials & tests to confirm the suitability of any product or system to their intended use. Our all recommendations or suggestions whether in technical documentations in writing or verbal are given in good faith but without any type of warranty or liability on us. We have no control over either the quality or condition of the substrate, or the factors affecting the use & applications of the product. Therefore we do not accept any liability arising from loss, injury or damage resulting from such uses.



The Ultimate Protective Solution

SWARAJ POLYCOATS

B – 53, STICE, Musalgaon, Tal- Sinnar, Dist- Nashik – 422103, Maharashtra, INDIA.
Telefax : +91-2551-240182. E-mail : swaraj.polycoats@gmail.com